| Directive EU 65/2014 – EN61591, EN60704-2-13, EN50554 | |
|---|--------|
| Brand SILVERLINE | |
| Model SL4240-90 | |
| Annual Energy Consumption (AEC)(kWh/a) | 85,634 |
| Energy Efficiency Class (EEI) | В |
| Fluid Dynamic Efficiency(FDE) | 23,349 |
| Fluid Dynamic Efficiency class (FDE) (Indice) | В |
| Light Efficiency (LE) | 24,833 |
| Lighting Efficiency Class (LE)(indice) | В |
| Grease Filtering Efficiency (GFE) | 76,1 |
| Grease Filtering Efficiency Class (GFE)(indice) | С |
| Minimum Air Flow in Normal Use MIN (m³/h) | 220 |
| Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m³/h) | 457 |
| Air Flow at Intensive/Boost Setting (m³/h) | 716 |
| Sound Power Level at Minimum Speed Avaible in Normal Use MIN (LwA)(dB) | 47 |
| Sound Power Level at Maximum Speed Avaible in Normal Use MAX (LwA)(dB) | 61 |
| Sound Power Level at Intensive/Boost Setting (LwA)(dB) | 70 |
| Power Consuption Off Mode (Po)(W) | 0,80 |
| Power Consuption in Standby Mode (Ps)(W) | - |
| Product Information compliant to commission regulation (EU) No 66/2014 | |
| Time increase factor (f) | 1,1595 |
| Energy Efficiency (EElhood) | 68,9 |
| Measured air flow rate at best efficiency point (QBEP)(m³/h) | 371,0 |
| Measured air pressure at best efficiency point (PBEP)(Pa) | 435 |
| Measured electric power input at best efficiency point (WBEP)(W) | 192,0 |
| Nominal power of the lighting system (W _{L)(W)} | 6,0 |
| Average illumination of the lighting system on the cooking surface (Emiddle)(lux) | 149 |