

| Directive EU 65/2014 – EN61591, EN60704-2-13, EN50554 | |
|--|---------------------|
| Brand | SILVERLINE |
| Model | SL 3122-80RF |
| Annual Energy Consumption (AEC)(kWh/a) | 52,038 |
| Energy Efficiency Class (EEI) | A |
| Fluid Dynamic Efficiency(FDE) | 31,845 |
| Fluid Dynamic Efficiency class (FDE) (Indice) | A |
| Light Efficiency (LE) | 34,667 |
| Lighting Efficiency Class (LE)(indice) | A |
| Grease Filtering Efficiency (GFE) | 77,0 |
| Grease Filtering Efficiency Class (GFE)(indice) | C |
| Minimum Air Flow in Normal Use MIN (m ³ /h) | 289 |
| Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m ³ /h) | 544 |
| Air Flow at Intensive/Boost Setting (m ³ /h) | 690 |
| Sound Power Level at Minimum Speed Available in Normal Use MIN (L _{WA})(dB) | 53 |
| Sound Power Level at Maximum Speed Available in Normal Use MAX (L _{WA})(dB) | 67 |
| Sound Power Level at Intensive/Boost Setting (L _{WA})(dB) | 72 |
| Power Consumption Off Mode (P _o)(W) | - |
| Power Consumption in Standby Mode (P _s)(W) | 0,69 |
| Product Information compliant to commission regulation (EU) No 66/2014 | |
| Time increase factor (f) | 0,8536 |
| Energy Efficiency (EELhood) | 49,6 |
| Measured air flow rate at best efficiency point (Q _{BEP})(m ³ /h) | 415,0 |
| Measured air pressure at best efficiency point (P _{BEP})(Pa) | 442 |
| Measured electric power input at best efficiency point (W _{BEP})(W) | 160,0 |
| Nominal power of the lighting system (W _L)(W) | 3,0 |
| Average illumination of the lighting system on the cooking surface (E _{middle})(lux) | 104 |