

Brand	<b>SILVERLINE</b>
Model	<b>SL3176-120 RF</b>
Annual Energy Consumption (AEC)(kWh/a)	<b>82</b>
Energy Efficiency Class (EEI)	<b>B</b>
Fluid Dynamic Efficiency(FDE)	<b>23,2</b>
Fluid Dynamic Efficiency class (FDE) (Indice)	<b>B</b>
Light Efficiency (LE)	<b>36</b>
Lighting Efficiency Class (LE)(indice)	<b>A</b>
Grease Filtering Efficiency (GFE)	<b>70</b>
Grease Filtering Efficiency Class (GFE)(indice)	<b>D</b>
Minimum Air Flow in Normal Use MIN (m <sup>3</sup> /h)	<b>196</b>
Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m <sup>3</sup> /h)	<b>439</b>
Air Flow at Intensive/Boost Setting (m <sup>3</sup> /h)	<b>658</b>
Sound Power Level at Minimum Speed Available in Normal Use MIN (L <sub>WA</sub> )(dB)	<b>46</b>
Sound Power Level at Maximum Speed Available in Normal Use MAX (L <sub>WA</sub> )(dB)	<b>58</b>
Sound Power Level at Intensive/Boost Setting (L <sub>WA</sub> )(dB)	<b>68</b>
Power Consumption Off Mode (P <sub>o</sub> )(W)	<b>0,80</b>
Power Consumption in Standby Mode (P <sub>s</sub> )(W)	<b>-</b>
<b>Product Information compliant to commission regulation (EU) No 66/2014</b>	
Time increase factor (f)	<b>1,1</b>
Energy Efficiency (EElhood)	<b>68</b>
Measured air flow rate at best efficiency point (Q <sub>BEP</sub> )(m <sup>3</sup> /h)	<b>368,0</b>
Measured air pressure at best efficiency point (P <sub>BEP</sub> )(Pa)	<b>420</b>
Measured electric power input at best efficiency point (W <sub>BEP</sub> )(W)	<b>185,0</b>
Nominal power of the lighting system (W <sub>L</sub> )(W)	<b>4,5</b>
Average illumination of the lighting system on the cooking surface (E <sub>middle</sub> )(lux)	<b>162</b>