

Brand	SILVERLINE
Model	SM 4142
Annual Energy Consumption (AEC)(kWh/a)	82
Energy Efficiency Class (EEI)	B
Fluid Dynamic Efficiency(FDE)	25,2
Fluid Dynamic Efficiency class (FDE) (Indice)	B
Light Efficiency (LE)	54
Lighting Efficiency Class (LE)(indice)	A
Grease Filtering Efficiency (GFE)	76
Grease Filtering Efficiency Class (GFE)(indice)	C
Minimum Air Flow in Normal Use MIN (m ³ /h)	205
Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m ³ /h)	648
Air Flow at Intensive/Boost Setting (m ³ /h)	-
Sound Power Level at Minimum Speed Available in Normal Use MIN (L _{WA})(dB)	56
Sound Power Level at Maximum Speed Available in Normal Use MAX (L _{WA})(dB)	60
Sound Power Level at Intensive/Boost Setting (L _{WA})(dB)	-
Power Consumption Off Mode (P _o)(W)	-
Power Consumption in Standby Mode (P _s)(W)	0,3
Product Information compliant to commission regulation (EU) No 66/2014	
Time increase factor (f)	1
Energy Efficiency (EElhood)	65
Measured air flow rate at best efficiency point (Q _{BEP})(m ³ /h)	423,0
Measured air pressure at best efficiency point (P _{BEP})(Pa)	421
Measured electric power input at best efficiency point (W _{BEP})(W)	196,0
Nominal power of the lighting system (W _L)(W)	6,0
Average illumination of the lighting system on the cooking surface (E _{middle})(lux)	325