

Directive EU 65/2014 – EN61591, EN60704-2-13, EN50554	
Brand	SILVERLINE
Model	SL4250-60 RF
Annual Energy Consumption (AEC)(kWh/a)	52,424
Energy Efficiency Class (EEI)	A
Fluid Dynamic Efficiency(FDE)	30,834
Fluid Dynamic Efficiency class (FDE) (Indice)	A
Light Efficiency (LE)	29,167
Lighting Efficiency Class (LE)(indice)	A
Grease Filtering Efficiency (GFE)	77,0
Grease Filtering Efficiency Class (GFE)(indice)	C
Minimum Air Flow in Normal Use MIN (m ³ /h)	280
Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m ³ /h)	535
Air Flow at Intensive/Boost Setting (m ³ /h)	680
Sound Power Level at Minimum Speed Available in Normal Use MIN (L _{WA})(dB)	47
Sound Power Level at Maximum Speed Available in Normal Use MAX (L _{WA})(dB)	58
Sound Power Level at Intensive/Boost Setting (L _{WA})(dB)	65
Power Consumption Off Mode (P _o)(W)	-
Power Consumption in Standby Mode (P _s)(W)	0,8
Product Information compliant to commission regulation (EU) No 66/2014	
Time increase factor (f)	0,89
Energy Efficiency (EELhood)	52,5
Measured air flow rate at best efficiency point (Q _{BEP})(m ³ /h)	359,4
Measured air pressure at best efficiency point (P _{BEP})(Pa)	456,8
Measured electric power input at best efficiency point (W _{BEP})(W)	147,9
Nominal power of the lighting system (W _L)(W)	6,0
Average illumination of the lighting system on the cooking surface (E _{middle})(lux)	175