

Brand	<b>SILVERLINE</b>
Model	<b>SL4250-90 SR</b>
Annual Energy Consumption (AEC)(kWh/a)	<b>54,228</b>
Energy Efficiency Class (EEI)	<b>A</b>
Fluid Dynamic Efficiency(FDE)	<b>31,845</b>
Fluid Dynamic Efficiency class (FDE) (Indice)	<b>A</b>
Light Efficiency (LE)	<b>28,167</b>
Lighting Efficiency Class (LE)(indice)	<b>A</b>
Grease Filtering Efficiency (GFE)	<b>77,0</b>
Grease Filtering Efficiency Class (GFE)(indice)	<b>C</b>
Minimum Air Flow in Normal Use MIN (m <sup>3</sup> /h)	<b>289</b>
Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m <sup>3</sup> /h)	<b>544</b>
Air Flow at Intensive/Boost Setting (m <sup>3</sup> /h)	<b>690</b>
Sound Power Level at Minimum Speed Available in Normal Use MIN (L <sub>WA</sub> )(dB)	<b>53</b>
Sound Power Level at Maximum Speed Available in Normal Use MAX (L <sub>WA</sub> )(dB)	<b>67</b>
Sound Power Level at Intensive/Boost Setting (L <sub>WA</sub> )(dB)	<b>72</b>
Power Consumption Off Mode (Po)(W)	<b>-</b>
Power Consumption in Standby Mode (Ps)(W)	<b>0,8</b>
<b>Product Information compliant to commission regulation (EU) No 66/2014</b>	
Time increase factor (f)	<b>0,8536</b>
Energy Efficiency (EElhood)	<b>50,9</b>
Measured air flow rate at best efficiency point (Q <sub>BEP</sub> )(m <sup>3</sup> /h)	<b>415,0</b>
Measured air pressure at best efficiency point (P <sub>BEP</sub> )(Pa)	<b>442</b>
Measured electric power input at best efficiency point (W <sub>BEP</sub> )(W)	<b>160,0</b>
Nominal power of the lighting system (W <sub>L</sub> )(W)	<b>6,0</b>
Average illumination of the lighting system on the cooking surface (E <sub>middle</sub> )(lux)	<b>169</b>