

**Produktblad vedrørende KOMMISSIONENS DELEGEREDE FORORDNING (EU) nr. 65/2014 af 1. oktober 2013 og KOMMISSIONENS DELEGEREDE FORORDNING (EU) nr. 66/2014 af 14 januar 2014**

Leverandørens navn eller varemærke	SMEG S.P.A.
Produktkod	KI120XE
Annual Efficiency Consumption (AEC <sub>hood</sub> )	63.6 kWh/year
Energy efficiency class (EEC)	B
Fluid Dynamic Efficiency (FDE)	28.7
Fluid Dynamic Efficiency class (FDEC)	A
Lighting Efficiency (LE)	70.9 lux/W
Lighting Efficiency Class (LEC)	A
Grease Filtering Efficiency (GFE)	83.9 %
Grease Filtering Efficiency Class (GFEC)	C
Air flow at minimum speed (Q <sub>min</sub> )	316 m <sup>3</sup> /h
Air flow at maximum speed (Q <sub>max</sub> )	529 m <sup>3</sup> /h
Air flow at boost speed (Q <sub>boost</sub> )	783 m <sup>3</sup> /h
Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE <sub>min</sub> )	48 dB(A)
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE <sub>max</sub> )	62 dB(A)
Airborne acoustical A-weighted sound power emission at boost speed (SPE <sub>boost</sub> )	70 dB(A)
Power consumption in stand-by mode (P <sub>s</sub> )	0.49 W
Time increase factor (F)	1.00
Energy Efficiency Index (EEI)	59
Measured air flow rate at best efficiency point (Q <sub>bep</sub> )	394 m <sup>3</sup> /h
Measured air pressure at best efficiency point (Q <sub>bep</sub> )	449 Pa
Measured electric power input at best efficiency point (W <sub>bep</sub> )	171 W
Normal Power of the light system (W <sub>l</sub> )	4 W
Average illumination of the light on the cooking surface (E <sub>middle</sub> )	312 lux
Sound power level at highest setting (L <sub>wa</sub> )	62 dB(A)

4. december 2017