

Directive EU 65/2014 – EN61591, EN60704-2-13, EN50554	
Brand	SILVERLINE
Model	SL 3122-90RF
Annual Energy Consumption (AEC)(kWh/a)	52,038
Energy Efficiency Class (EEI)	A
Fluid Dynamic Efficiency(FDE)	31,845
Fluid Dynamic Efficiency class (FDE) (Indice)	A
Light Efficiency (LE)	34,667
Lighting Efficiency Class (LE)(indice)	A
Grease Filtering Efficiency (GFE)	77,0
Grease Filtering Efficiency Class (GFE)(indice)	C
Minimum Air Flow in Normal Use MIN (m ³ /h)	289
Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m ³ /h)	544
Air Flow at Intensive/Boost Setting (m ³ /h)	690
Sound Power Level at Minimum Speed Available in Normal Use MIN (L _{WA})(dB)	53
Sound Power Level at Maximum Speed Available in Normal Use MAX (L _{WA})(dB)	67
Sound Power Level at Intensive/Boost Setting (L _{WA})(dB)	72
Power Consumption Off Mode (P _o)(W)	-
Power Consumption in Standby Mode (P _s)(W)	0,69
Product Information compliant to commission regulation (EU) No 66/2014	
Time increase factor (f)	0,8536
Energy Efficiency (EELhood)	49,6
Measured air flow rate at best efficiency point (Q _{BEP})(m ³ /h)	415,0
Measured air pressure at best efficiency point (P _{BEP})(Pa)	442
Measured electric power input at best efficiency point (W _{BEP})(W)	160,0
Nominal power of the lighting system (W _L)(W)	3,0
Average illumination of the lighting system on the cooking surface (E _{middle})(lux)	104